

# High Capacitance Capacitors

## ■ HOW TO ORDER

1206	F	106	Z	100	C	T
Size	Dielectric	Capacitance	Tolerance	Rated voltage	Termination	Packaging
Inch (mm) 0402 (1005) 0603 (1608) 0805 (2012) 1206 (3216) 1210 (3225) 1812 (4532)	B=X7R X=X5R S=X6S F=Y5V	Two significant digits followed by no. of zeros. And R is in place of decimal point.  eg.: 106=10x10 <sup>6</sup> =10μF	K=±10% M=±20% Z=-20/+80%	Two significant digits followed by no. of zeros. And R is in place of decimal point.  6R3=6.3 VDC 100=10 VDC 160=16 VDC 250=25 VDC 500=50 VDC	C=Cu/Ni/Sn	B=Bulk C=Bulk cassette T=7" reeled G=13" reeled

## ■ PACKAGING DIMENSION AND QUANTITY

Size	Thickness (mm)/Symbol		Paper tape		Plastic tape	
			7" reel	13" reel	7" reel	13" reel
0402 (1005)	0.50±0.05	N	10k	50k	-	-
0603 (1608)	0.80±0.07	S	4k	15k	-	-
	0.80+0.15/-0.10	X	4k	15k	-	-
0805 (2012)	0.80±0.10	B	4k	15k	-	-
	1.25±0.10	D	-	-	3k	10k
	1.25±0.20	I	-	-	3k	10k
1206 (3216)	0.95±0.10	C	-	-	3k	10k
	1.15±0.15	J	-	-	3k	10k
	1.60±0.20	G	-	-	2k	-
	1.60+0.30/-0.10	P	-	-	2k	-
1210 (3225)	0.95±0.10	C	-	-	3k	10k
	1.25±0.10	D	-	-	3k	10k
	1.60±0.20	G	-	-	2k	-
	2.00±0.20	K	-	-	1k	-
1812 (4532)	1.25±0.10	D	-	-	1k	-
	2.00±0.20	K	-	-	1k	-

Unit: pieces

# High Capacitance Capacitors

## ■ CAPACITANCE RANGE

### X7R Dielectric

Dielectric		X7R																	
Size		0402				0603			0805			1206				1210		1812	
Rated Voltage (VDC)		10	10	16	25	50	10	16	25	10	16	25	50	25	50	25	50		
Capacitance	0.10 $\mu$ F (104)	N		S	S	X													
	0.15 $\mu$ F (154)		S	S															
	0.22 $\mu$ F (224)		S	S															
	0.33 $\mu$ F (334)		X	X															
	0.47 $\mu$ F (474)		X	X															
	0.68 $\mu$ F (684)																		
	1.0 $\mu$ F (105)		X				D	D	D		J	J	P	D	D	D	K		
	1.5 $\mu$ F (155)																		
	2.2 $\mu$ F (225)									J	J	P		G					
3.3 $\mu$ F (335)									P										
4.7 $\mu$ F (475)									P										

1. The letter in cell is expressed the symbol of product thickness.
2. For more information about products with special capacitance or other data, please contact WTC local representative.

### X5R Dielectric

Dielectric		X5R									
Size		0402			0603			0805	1206		
Rated Voltage (VDC)		6.3	10	16	6.3	10	16	6.3	6.3	10	16
Capacitance	0.027 $\mu$ F (273)			N							
	0.033 $\mu$ F (333)			N							
	0.039 $\mu$ F (393)			N							
	0.047 $\mu$ F (473)			N							
	0.056 $\mu$ F (563)		N	N							
	0.068 $\mu$ F (683)		N	N							
	0.082 $\mu$ F (823)		N	N							
	0.10 $\mu$ F (104)		N	N							
	0.15 $\mu$ F (154)										
	0.22 $\mu$ F (224)	N*									
	0.33 $\mu$ F (334)					X	X				
	0.47 $\mu$ F (474)					X	X				
	0.68 $\mu$ F (684)					X	X	X			
	1.0 $\mu$ F (105)					X	X				
	1.5 $\mu$ F (155)										J
	2.2 $\mu$ F (225)								I		J
3.3 $\mu$ F (335)										P	
4.7 $\mu$ F (475)									I	P	
6.8 $\mu$ F (685)									P	P	
10 $\mu$ F (106)									I	P	

1. The letter in cell is expressed the symbol of product thickness.
2. The letter in cell with "\*" mark is expressed product also available for X6S dielectric.
3. The shadow cell is expressed that product is under development, please contact WTC local representative to inquire more information.

### Y5V Dielectric

Dielectric		Y5V																	
Size		0402		0603		0805			1206				1210				1812		
Rated Voltage (VDC)		6.3	10	10	16	10	16	25	10	16	25	50	10	16	25	35	50	25	50
Capacitance	0.15 $\mu$ F (154)		N																
	0.22 $\mu$ F (224)		N																
	0.33 $\mu$ F (334)	N																	
	0.47 $\mu$ F (474)	N																	
	0.68 $\mu$ F (684)	N																	
	1.0 $\mu$ F (105)	N		S	X	B	B	D		C	C	C					C		D
	1.5 $\mu$ F (155)			S		D	D			C	C				C				D
	2.2 $\mu$ F (225)			S		D	D			C	C				C				D
	3.3 $\mu$ F (335)					D	D		J	J	J				C				D
	4.7 $\mu$ F (475)					D	D		J	J	J			C	D				D
	6.8 $\mu$ F (685)					I			J	J				C	G				D
	10 $\mu$ F (106)					I			J	J				D	G	K		D	
	22 $\mu$ F (226)								P					K					
	47 $\mu$ F (476)													K					

1. The letter in cell is expressed the symbol of product thickness.
2. For more information about products with special capacitance or other data, please contact WTC local representative.

# Appendix I : Reliability Test Conditions and Requirements

NO.	Item	Test Condition	Requirements																																																																
1.	Visual and Mechanical	---	<ul style="list-style-type: none"> <li>* No remarkable defect.</li> <li>* Dimensions to confirm to individual specification sheet.</li> </ul>																																																																
2.	Capacitance	Class I : NPO Cap 1000pF 1.0±0.2Vrms, 1MHz±10%	<ul style="list-style-type: none"> <li>* Shall not exceed the limits given in the detailed spec.</li> </ul> <p>NPO: Cap 30pF, Q 1000; Cap&lt;30pF, Q 400+20C X7R, X5R:</p> <table border="1"> <thead> <tr> <th>Rated vol.</th> <th>D.F.</th> <th colspan="2">Exception of D.F.</th> </tr> </thead> <tbody> <tr> <td rowspan="2">50V</td> <td rowspan="2">2.5%</td> <td>3.0%</td> <td>All 0201:0603 0.047µF;0805 0.18µF; 1206 0.47µF</td> </tr> <tr> <td>7.0%</td> <td>0603 0.33µF;TT series &amp; Cap 1µF</td> </tr> <tr> <td rowspan="2">25V</td> <td rowspan="2">3.5%</td> <td>5.0%</td> <td>0805 1µF, 1210 10µF</td> </tr> <tr> <td>10%</td> <td>0603 0.33µF;0603 0.15µF; 0805 0.68µF;1206 2.2µF</td> </tr> <tr> <td>16V</td> <td>3.5%</td> <td>5.0%</td> <td>TT series &amp; Cap 1µF</td> </tr> <tr> <td>10V</td> <td>5.0%</td> <td>10.0%</td> <td>TT series &amp; Cap 1µF;0805 10µF</td> </tr> <tr> <td>6.3V</td> <td>10.0%</td> <td>15.0%</td> <td>0805 22µF;1210 100µF</td> </tr> </tbody> </table> <p>Y5V:</p> <table border="1"> <thead> <tr> <th>Rated vol.</th> <th>D.F.</th> <th colspan="2">Exception of D.F.</th> </tr> </thead> <tbody> <tr> <td>50V</td> <td>5.0%</td> <td>---</td> <td>---</td> </tr> <tr> <td rowspan="2">35V</td> <td rowspan="2">7.0%</td> <td>---</td> <td>---</td> </tr> <tr> <td>---</td> <td>---</td> </tr> <tr> <td rowspan="2">25V</td> <td rowspan="2">5.0%</td> <td>7.0%</td> <td>0603 0.1µF; 0805 0.33µF; 1206 1µF; 1210 4.7µF</td> </tr> <tr> <td>9.0%</td> <td>0402 0.068µF</td> </tr> <tr> <td>16V (C&lt;1.0µF)</td> <td>7.0%</td> <td>9.0%</td> <td>0402 0.068µF; 0603 0.68µF</td> </tr> <tr> <td>16V (C 1.0µF)</td> <td>9.0%</td> <td>12.5%</td> <td>0805 4.7µF;1206 10µF;1210 22µF</td> </tr> <tr> <td>10V</td> <td>12.5%</td> <td>---</td> <td>---</td> </tr> <tr> <td>6.3V</td> <td>20.0%</td> <td>---</td> <td>---</td> </tr> </tbody> </table>	Rated vol.	D.F.	Exception of D.F.		50V	2.5%	3.0%	All 0201:0603 0.047µF;0805 0.18µF; 1206 0.47µF	7.0%	0603 0.33µF;TT series & Cap 1µF	25V	3.5%	5.0%	0805 1µF, 1210 10µF	10%	0603 0.33µF;0603 0.15µF; 0805 0.68µF;1206 2.2µF	16V	3.5%	5.0%	TT series & Cap 1µF	10V	5.0%	10.0%	TT series & Cap 1µF;0805 10µF	6.3V	10.0%	15.0%	0805 22µF;1210 100µF	Rated vol.	D.F.	Exception of D.F.		50V	5.0%	---	---	35V	7.0%	---	---	---	---	25V	5.0%	7.0%	0603 0.1µF; 0805 0.33µF; 1206 1µF; 1210 4.7µF	9.0%	0402 0.068µF	16V (C<1.0µF)	7.0%	9.0%	0402 0.068µF; 0603 0.68µF	16V (C 1.0µF)	9.0%	12.5%	0805 4.7µF;1206 10µF;1210 22µF	10V	12.5%	---	---	6.3V	20.0%	---	---
Rated vol.	D.F.	Exception of D.F.																																																																	
50V	2.5%	3.0%	All 0201:0603 0.047µF;0805 0.18µF; 1206 0.47µF																																																																
		7.0%	0603 0.33µF;TT series & Cap 1µF																																																																
25V	3.5%	5.0%	0805 1µF, 1210 10µF																																																																
		10%	0603 0.33µF;0603 0.15µF; 0805 0.68µF;1206 2.2µF																																																																
16V	3.5%	5.0%	TT series & Cap 1µF																																																																
10V	5.0%	10.0%	TT series & Cap 1µF;0805 10µF																																																																
6.3V	10.0%	15.0%	0805 22µF;1210 100µF																																																																
Rated vol.	D.F.	Exception of D.F.																																																																	
50V	5.0%	---	---																																																																
35V	7.0%	---	---																																																																
		---	---																																																																
25V	5.0%	7.0%	0603 0.1µF; 0805 0.33µF; 1206 1µF; 1210 4.7µF																																																																
		9.0%	0402 0.068µF																																																																
16V (C<1.0µF)	7.0%	9.0%	0402 0.068µF; 0603 0.68µF																																																																
16V (C 1.0µF)	9.0%	12.5%	0805 4.7µF;1206 10µF;1210 22µF																																																																
10V	12.5%	---	---																																																																
6.3V	20.0%	---	---																																																																
3.	Q/ D.F. (Dissipation Factor)	Class II : X7R, X5R, Y5V Cap 10µF, 1.0±0.2Vrms, 1KHz±10% Cap>10µF, 0.5±0.2Vrms, 120Hz±20%																																																																	
4a.	Dielectric Strength	<ul style="list-style-type: none"> <li>* To apply voltage ( 50V) 250%.</li> <li>* Duration : 1 to 5 sec.</li> <li>* Charge &amp; discharge current less than 50mA.</li> </ul> <table border="1"> <thead> <tr> <th>To apply voltage :</th> <th></th> </tr> </thead> <tbody> <tr> <td>100V</td> <td>3 times V DC</td> </tr> <tr> <td>200V ~ 300V</td> <td>2 times V DC</td> </tr> <tr> <td>500V ~ 999V</td> <td>1.5 times V DC</td> </tr> <tr> <td>1000V ~ 3000V</td> <td>1.2 times V DC</td> </tr> </tbody> </table> <ul style="list-style-type: none"> <li>* Cut-off, set at 10mA</li> <li>* TEST= 15 sec.</li> <li>* RAMP=0</li> </ul>	To apply voltage :		100V	3 times V DC	200V ~ 300V	2 times V DC	500V ~ 999V	1.5 times V DC	1000V ~ 3000V	1.2 times V DC	<ul style="list-style-type: none"> <li>* No evidence of damage or flash over during test.</li> </ul>																																																						
To apply voltage :																																																																			
100V	3 times V DC																																																																		
200V ~ 300V	2 times V DC																																																																		
500V ~ 999V	1.5 times V DC																																																																		
1000V ~ 3000V	1.2 times V DC																																																																		
4b.	Dielectric Strength (for X1/Y2 & X2/Y3)	<ul style="list-style-type: none"> <li>* To apply 1500 VAC voltage.</li> <li>* Duration: 60 sec.</li> </ul>	<ul style="list-style-type: none"> <li>* No evidence of damage or flash over during test.</li> </ul>																																																																
5.	Insulation Resistance	To apply rated voltage for max. 120 sec.	10G or RxC 500 -F whichever is smaller.																																																																
		Rated voltage: 100 ~ 500V	To apply rated voltage for 60 sec.	10G																																																															
		Rated voltage: > 500V	To apply 500V for 60 sec.	10G																																																															
6.	Temperature Coefficient	<p>With no electrical load.</p> <table border="1"> <thead> <tr> <th>T.C.</th> <th>Operating Temp</th> </tr> </thead> <tbody> <tr> <td>NPO (COG)</td> <td>-55~125°C at 25°C</td> </tr> <tr> <td>NPO (COJ)</td> <td>-55~125°C at 25°C</td> </tr> <tr> <td>X7R</td> <td>-55~125°C at 25°C</td> </tr> <tr> <td>X5R</td> <td>-55~85°C at 25°C</td> </tr> <tr> <td>Y5V</td> <td>-25~85°C at 20°C</td> </tr> </tbody> </table>	T.C.	Operating Temp	NPO (COG)	-55~125°C at 25°C	NPO (COJ)	-55~125°C at 25°C	X7R	-55~125°C at 25°C	X5R	-55~85°C at 25°C	Y5V	-25~85°C at 20°C	<table border="1"> <thead> <tr> <th>T.C.</th> <th>Capacitance Change</th> </tr> </thead> <tbody> <tr> <td>NPO (COG)</td> <td>Within ±30ppm/°C</td> </tr> <tr> <td>NPO (COJ)</td> <td>Within ±120ppm/°C</td> </tr> <tr> <td>X7R</td> <td>Within ±15%</td> </tr> <tr> <td>X5R</td> <td>Within ±15%</td> </tr> <tr> <td>Y5V</td> <td>Within +30%/-80%</td> </tr> </tbody> </table>	T.C.	Capacitance Change	NPO (COG)	Within ±30ppm/°C	NPO (COJ)	Within ±120ppm/°C	X7R	Within ±15%	X5R	Within ±15%	Y5V	Within +30%/-80%																																								
T.C.	Operating Temp																																																																		
NPO (COG)	-55~125°C at 25°C																																																																		
NPO (COJ)	-55~125°C at 25°C																																																																		
X7R	-55~125°C at 25°C																																																																		
X5R	-55~85°C at 25°C																																																																		
Y5V	-25~85°C at 20°C																																																																		
T.C.	Capacitance Change																																																																		
NPO (COG)	Within ±30ppm/°C																																																																		
NPO (COJ)	Within ±120ppm/°C																																																																		
X7R	Within ±15%																																																																		
X5R	Within ±15%																																																																		
Y5V	Within +30%/-80%																																																																		
7.	Adhesive Strength of Termination	<ul style="list-style-type: none"> <li>* Pressurizing force: 0201: 2N 0402 &amp; 0603: 5N &gt;0603: 10N</li> <li>* Test time: 10±1 sec.</li> </ul>	<ul style="list-style-type: none"> <li>* No remarkable damage or removal of the terminations.</li> </ul>																																																																
8.	Vibration Resistance	<ul style="list-style-type: none"> <li>* Vibration frequency: 10~55 Hz/min.</li> <li>* Total amplitude: 1.5mm</li> <li>* Test time: 6 hrs. (Two hrs each in three mutually perpendicular directions.)</li> </ul>	<ul style="list-style-type: none"> <li>* No remarkable damage.</li> <li>* Cap change and Q/D.F.: To meet initial spec.</li> </ul>																																																																

# Appendix I : Reliability Test Conditions and Requirements

NO.	Item	Test Condition	Requirements																																																										
9.	Solderability	<ul style="list-style-type: none"> <li>* Solder temperature: 235±5°C</li> <li>* Dipping time: 2±0.5 sec.</li> </ul>	95% min. coverage of all metalized area.																																																										
10.	Bending Test	<ul style="list-style-type: none"> <li>* The middle part of substrate shall be pressurized by means of the pressurizing rod at a rate of about 1 mm per second until the deflection becomes 1 mm and then the pressure shall be maintained for 5±1 sec.</li> <li>* Measurement to be made after keeping at room temp. for 24±2 hrs.</li> </ul>	<ul style="list-style-type: none"> <li>* No remarkable damage.</li> <li>* Cap change: NPO: within ±5.0% or ±0.5pF whichever is larger. X7R, X5R: within ±12.5% Y5V: within ±30% (This capacitance change means the change of capacitance under specified flexure of substrate from the capacitance measured before the test.)</li> </ul>																																																										
11.	Resistance to Soldering Heat	<ul style="list-style-type: none"> <li>* Solder temperature: 270±5°C</li> <li>* Dipping time: 10±1 sec</li> <li>* Preheating: 120 to 150°C for 1 minute before immerse the capacitor in an eutectic solder.</li> <li>* Before initial measurement (Class II only): Perform 150+0/-10°C for 1 hr and then set for 48±4 hrs at room temp.</li> <li>* Measurement to be made after keeping at room temp. for 24±2 hrs. (Class I) or 48±4 hrs. (Class II).</li> </ul>	<ul style="list-style-type: none"> <li>* No remarkable damage.</li> <li>* Cap change: NPO: within ±2.5% or ±0.25pF whichever is larger. X7R, X5R: within ±7.5% Y5V: within ±20%</li> <li>* Q/D.F., I.R. and dielectric strength: To meet initial requirements.</li> <li>* 25% max. leaching on each edge.</li> </ul>																																																										
12.	Temperature Cycle	<ul style="list-style-type: none"> <li>* Conduct the five cycles according to the temperatures and time.</li> </ul> <table border="1"> <thead> <tr> <th>Step</th> <th>Temp. (°C)</th> <th>Time (min.)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Min. operating temp. +0/-3</td> <td>30±3</td> </tr> <tr> <td>2</td> <td>Room temp.</td> <td>2-3</td> </tr> <tr> <td>3</td> <td>Max. operating temp. +3/-0</td> <td>30±3</td> </tr> <tr> <td>4</td> <td>Room temp.</td> <td>2-3</td> </tr> </tbody> </table> <ul style="list-style-type: none"> <li>* Before initial measurement (Class II only): Perform 150+0/-10°C for 1 hr and then set for 48±4 hrs at room temp.</li> <li>* Measurement to be made after keeping at room temp. for 24±2 hrs. (Class I) or 48±4 hrs. (Class II).</li> </ul>	Step	Temp. (°C)	Time (min.)	1	Min. operating temp. +0/-3	30±3	2	Room temp.	2-3	3	Max. operating temp. +3/-0	30±3	4	Room temp.	2-3	<ul style="list-style-type: none"> <li>* No remarkable damage.</li> <li>* Cap change: NPO: within ±2.5% or ±0.25pF whichever is larger. X7R, X5R: within ±7.5% Y5V: within ±20%</li> <li>* Q/D.F., I.R. and dielectric strength: To meet initial requirements.</li> </ul>																																											
Step	Temp. (°C)	Time (min.)																																																											
1	Min. operating temp. +0/-3	30±3																																																											
2	Room temp.	2-3																																																											
3	Max. operating temp. +3/-0	30±3																																																											
4	Room temp.	2-3																																																											
13.	Humidity (Steady State)	<ul style="list-style-type: none"> <li>* Test temp.: 40±2°C</li> <li>* Humidity: 90~95% RH</li> <li>* Test time: 500+24/-0hrs.</li> <li>* Measurement to be made after keeping at room temp. for 24±2 hrs. (Class I) or 48±4 hrs. (Class II).</li> </ul>	<ul style="list-style-type: none"> <li>* No remarkable damage.</li> <li>* Cap change: NPO: within ±5.0% or ±0.5pF whichever is larger. X7R, X5R: 10V, within ±12.5% 6.3V, within ±25% Y5V: within ±30%</li> <li>* Q/D.F. value: NPO: Cap 30pF, Q 350; 10pF Cap&lt;30pF, Q 275+2.5C Cap&lt;10pF; Q 200+10C X7R, X5R:</li> </ul> <table border="1"> <thead> <tr> <th>Rated vol.</th> <th>D.F.</th> <th colspan="2">Exception of D.F.</th> </tr> </thead> <tbody> <tr> <td>50V</td> <td>3.0%</td> <td>6.0%</td> <td>0603 0.047µF; 0805 0.18µF; 1206 0.47µF</td> </tr> <tr> <td rowspan="2">25V</td> <td rowspan="2">5.0%</td> <td>10.0%</td> <td>0805 1µF; 1210 10µF</td> </tr> <tr> <td>14.0%</td> <td>0603 0.33µF</td> </tr> <tr> <td rowspan="2">16V</td> <td rowspan="2">5.0%</td> <td>10.0%</td> <td>0402 0.033µF; 0603 0.15µF; 0805 0.68µF; 1206 2.2µF</td> </tr> <tr> <td>15.0%</td> <td>0402 0.056µF; 0603 0.33µF; 0805 2.2µF; 1206 2.2µF, TT series &amp; Cap 1µF</td> </tr> <tr> <td>6.3V</td> <td>15.0%</td> <td>30.0%</td> <td>0805 10µF; 1210 100µF</td> </tr> </tbody> </table> <p>Y5V:</p> <table border="1"> <thead> <tr> <th>Rated vol.</th> <th>D.F.</th> <th colspan="2">Exception of D.F.</th> </tr> </thead> <tbody> <tr> <td>50V</td> <td>7.5%</td> <td>---</td> <td>---</td> </tr> <tr> <td>35V</td> <td>10.0%</td> <td>---</td> <td>---</td> </tr> <tr> <td rowspan="2">25V</td> <td rowspan="2">7.5%</td> <td>10.0%</td> <td>0603 0.1µF; 0805 0.33µF; 1206 1µF; 1210 4.7µF</td> </tr> <tr> <td>12.5%</td> <td>0402 0.068µF</td> </tr> <tr> <td>16V (C&lt;1.0µF)</td> <td>10.0%</td> <td>12.5%</td> <td>0402 0.068µF; 0603 0.68µF</td> </tr> <tr> <td>16V (C 1.0µF)</td> <td>12.5%</td> <td>---</td> <td>---</td> </tr> <tr> <td>10V</td> <td>15.0%</td> <td>---</td> <td>---</td> </tr> <tr> <td>6.3V</td> <td>30.0%</td> <td>---</td> <td>---</td> </tr> </tbody> </table> <ul style="list-style-type: none"> <li>* I.R.: 10V 1G or 50 -F whichever is smaller. 6.3V, 10 -F</li> </ul>	Rated vol.	D.F.	Exception of D.F.		50V	3.0%	6.0%	0603 0.047µF; 0805 0.18µF; 1206 0.47µF	25V	5.0%	10.0%	0805 1µF; 1210 10µF	14.0%	0603 0.33µF	16V	5.0%	10.0%	0402 0.033µF; 0603 0.15µF; 0805 0.68µF; 1206 2.2µF	15.0%	0402 0.056µF; 0603 0.33µF; 0805 2.2µF; 1206 2.2µF, TT series & Cap 1µF	6.3V	15.0%	30.0%	0805 10µF; 1210 100µF	Rated vol.	D.F.	Exception of D.F.		50V	7.5%	---	---	35V	10.0%	---	---	25V	7.5%	10.0%	0603 0.1µF; 0805 0.33µF; 1206 1µF; 1210 4.7µF	12.5%	0402 0.068µF	16V (C<1.0µF)	10.0%	12.5%	0402 0.068µF; 0603 0.68µF	16V (C 1.0µF)	12.5%	---	---	10V	15.0%	---	---	6.3V	30.0%	---	---
Rated vol.	D.F.	Exception of D.F.																																																											
50V	3.0%	6.0%	0603 0.047µF; 0805 0.18µF; 1206 0.47µF																																																										
25V	5.0%	10.0%	0805 1µF; 1210 10µF																																																										
		14.0%	0603 0.33µF																																																										
16V	5.0%	10.0%	0402 0.033µF; 0603 0.15µF; 0805 0.68µF; 1206 2.2µF																																																										
		15.0%	0402 0.056µF; 0603 0.33µF; 0805 2.2µF; 1206 2.2µF, TT series & Cap 1µF																																																										
6.3V	15.0%	30.0%	0805 10µF; 1210 100µF																																																										
Rated vol.	D.F.	Exception of D.F.																																																											
50V	7.5%	---	---																																																										
35V	10.0%	---	---																																																										
25V	7.5%	10.0%	0603 0.1µF; 0805 0.33µF; 1206 1µF; 1210 4.7µF																																																										
		12.5%	0402 0.068µF																																																										
16V (C<1.0µF)	10.0%	12.5%	0402 0.068µF; 0603 0.68µF																																																										
16V (C 1.0µF)	12.5%	---	---																																																										
10V	15.0%	---	---																																																										
6.3V	30.0%	---	---																																																										


# Appendix I : Reliability Test Conditions and Requirements

NO.	Item	Test Condition	Requirements																																																										
14.	Humidity Load (Damp Heat)	<ul style="list-style-type: none"> <li>* Test temp.: 40±2°C</li> <li>* Humidity: 90~95%RH</li> <li>* Test time: 500+24/-0 hrs.</li> <li>* To apply voltage: rated voltage (Max. 500V)</li> <li>* Measurement to be made after keeping at room temp. for 24±2 hrs. (Class I) or 48±4 hrs. (Class II).</li> </ul>	<ul style="list-style-type: none"> <li>* No remarkable damage.</li> <li>* Cap change: NPO: within ±7.5% or ±0.75pF whichever is larger. X7R, X5R: 10V, within ±12.5% 6.3V, with ±25% Y5V: 10V, within ±30% 6.3V, within +30 to -40%</li> <li>* Q/D.F. value: NPO: Cap 30pF, Q 200; Cap&lt;30pF, Q 100+10/3C X7R, X5R:</li> </ul> <table border="1"> <thead> <tr> <th>Rated vol.</th> <th>D.F.</th> <th colspan="2">Exception of D.F.</th> </tr> </thead> <tbody> <tr> <td>50V</td> <td>3.0%</td> <td>6.0%</td> <td>0603 0.047µF; 0805 0.18µF; 1206 0.47µF</td> </tr> <tr> <td rowspan="2">25V</td> <td rowspan="2">5.0%</td> <td>10.0%</td> <td>0805 1µF, 1210 10µF</td> </tr> <tr> <td>14.0%</td> <td>0603 0.33µF</td> </tr> <tr> <td rowspan="2">16V</td> <td rowspan="2">5.0%</td> <td>10.0%</td> <td>0402 0.033µF; 0603 0.15µF; 0805 0.68µF; 1206 2.2µF</td> </tr> <tr> <td>15.0%</td> <td>0402 0.056µF; 0603 0.33µF; 0805 2.2µF; 1206 2.2µF, TT series &amp; Cap 1µF</td> </tr> <tr> <td>6.3V</td> <td>15.0%</td> <td>30.0%</td> <td>0805 10µF; 1210 100µF</td> </tr> </tbody> </table> <p>Y5V:</p> <table border="1"> <thead> <tr> <th>Rated vol.</th> <th>D.F.</th> <th colspan="2">Exception of D.F.</th> </tr> </thead> <tbody> <tr> <td>50V</td> <td>7.5%</td> <td>---</td> <td>---</td> </tr> <tr> <td>35V</td> <td>10.0%</td> <td>---</td> <td>---</td> </tr> <tr> <td rowspan="2">25V</td> <td rowspan="2">7.5%</td> <td>10.0%</td> <td>0603 0.1µF; 0805 0.33µF; 1206 1µF; 1210 4.7µF</td> </tr> <tr> <td>12.5%</td> <td>0402 0.068µF</td> </tr> <tr> <td>16V (C&lt;1.0µF)</td> <td>10.0%</td> <td>12.5%</td> <td>0402 0.068µF; 0603 0.68µF</td> </tr> <tr> <td>16V (C 1.0µF)</td> <td>12.5%</td> <td>---</td> <td>---</td> </tr> <tr> <td>10V</td> <td>15.0%</td> <td>---</td> <td>---</td> </tr> <tr> <td>6.3V</td> <td>30.0%</td> <td>---</td> <td>---</td> </tr> </tbody> </table> <ul style="list-style-type: none"> <li>* I.R.: 10V, 500M or 25 -F whichever is smaller. 6.3V, 5 -F</li> </ul>	Rated vol.	D.F.	Exception of D.F.		50V	3.0%	6.0%	0603 0.047µF; 0805 0.18µF; 1206 0.47µF	25V	5.0%	10.0%	0805 1µF, 1210 10µF	14.0%	0603 0.33µF	16V	5.0%	10.0%	0402 0.033µF; 0603 0.15µF; 0805 0.68µF; 1206 2.2µF	15.0%	0402 0.056µF; 0603 0.33µF; 0805 2.2µF; 1206 2.2µF, TT series & Cap 1µF	6.3V	15.0%	30.0%	0805 10µF; 1210 100µF	Rated vol.	D.F.	Exception of D.F.		50V	7.5%	---	---	35V	10.0%	---	---	25V	7.5%	10.0%	0603 0.1µF; 0805 0.33µF; 1206 1µF; 1210 4.7µF	12.5%	0402 0.068µF	16V (C<1.0µF)	10.0%	12.5%	0402 0.068µF; 0603 0.68µF	16V (C 1.0µF)	12.5%	---	---	10V	15.0%	---	---	6.3V	30.0%	---	---
Rated vol.	D.F.	Exception of D.F.																																																											
50V	3.0%	6.0%	0603 0.047µF; 0805 0.18µF; 1206 0.47µF																																																										
25V	5.0%	10.0%	0805 1µF, 1210 10µF																																																										
		14.0%	0603 0.33µF																																																										
16V	5.0%	10.0%	0402 0.033µF; 0603 0.15µF; 0805 0.68µF; 1206 2.2µF																																																										
		15.0%	0402 0.056µF; 0603 0.33µF; 0805 2.2µF; 1206 2.2µF, TT series & Cap 1µF																																																										
6.3V	15.0%	30.0%	0805 10µF; 1210 100µF																																																										
Rated vol.	D.F.	Exception of D.F.																																																											
50V	7.5%	---	---																																																										
35V	10.0%	---	---																																																										
25V	7.5%	10.0%	0603 0.1µF; 0805 0.33µF; 1206 1µF; 1210 4.7µF																																																										
		12.5%	0402 0.068µF																																																										
16V (C<1.0µF)	10.0%	12.5%	0402 0.068µF; 0603 0.68µF																																																										
16V (C 1.0µF)	12.5%	---	---																																																										
10V	15.0%	---	---																																																										
6.3V	30.0%	---	---																																																										
15.	High Temperature Load (Endurance)	<ul style="list-style-type: none"> <li>* Test temp.: NPO, X7R: 125±3°C X5R, Y5V: 85±3°C</li> <li>* To apply voltage: (1) 6.3V or C 10µF (for X7R, X5R): 150% of rated voltage. (2) 6.3V&lt;V&lt;500V and C&lt;10µF (for X7R, X5R): 200% of rated voltage. (3) 500V: 150% of rated voltage. (4) V 630V: 120% of rated voltage. (Max. 3600V)</li> <li>* Test time: 1000+24/-0 hrs.</li> <li>* Measurement to be made after keeping at room temp. for 24±2 hrs. (Class I) or 48±4 hrs. (Class II).</li> </ul>	<ul style="list-style-type: none"> <li>* No remarkable damage.</li> <li>* Cap change: NPO: within ±3.0% or ±0.3pF whichever is larger. X7R, X5R: 10V, within ±12.5% 6.3V, with ±25% Y5V: 10V, within ±30% 6.3V, within +30 to -40%</li> <li>* Q/D.F. value: NPO: Cap 30pF, Q 350 10pF Cap&lt;30pF, Q 275+2.5C Cap&lt;10pF, Q 200+10C X7R, X5R:</li> </ul> <table border="1"> <thead> <tr> <th>Rated vol.</th> <th>D.F.</th> <th colspan="2">Exception of D.F.</th> </tr> </thead> <tbody> <tr> <td>50V</td> <td>3.0%</td> <td>6.0%</td> <td>0603 0.047µF; 0805 0.18µF, 1206 0.47µF</td> </tr> <tr> <td rowspan="2">25V</td> <td rowspan="2">5.0%</td> <td>10.0%</td> <td>0805 1µF, 1210 10µF</td> </tr> <tr> <td>14.0%</td> <td>0603 0.33µF</td> </tr> <tr> <td rowspan="2">16V</td> <td rowspan="2">5.0%</td> <td>10.0%</td> <td>0402 0.033µF; 0603 0.15µF; 0805 0.68µF; 1206 2.2µF</td> </tr> <tr> <td>15.0%</td> <td>0402 0.056µF; 0603 0.33µF; 0805 2.2µF; 1206 2.2µF TT series &amp; Cap 1µF</td> </tr> <tr> <td>6.3V</td> <td>15.0%</td> <td>30.0%</td> <td>0805 10µF; 1210 100µF</td> </tr> </tbody> </table> <p>Y5V:</p> <table border="1"> <thead> <tr> <th>Rated vol.</th> <th>D.F.</th> <th colspan="2">Exception of D.F.</th> </tr> </thead> <tbody> <tr> <td>50V</td> <td>7.5%</td> <td>---</td> <td>---</td> </tr> <tr> <td>35V</td> <td>10.0%</td> <td>---</td> <td>---</td> </tr> <tr> <td rowspan="2">25V</td> <td rowspan="2">7.5%</td> <td>10.0%</td> <td>0603 0.1µF; 0805 0.33µF; 1206 1µF; 1210 4.7µF</td> </tr> <tr> <td>12.5%</td> <td>0402 0.068µF</td> </tr> <tr> <td>16V (C&lt;1.0µF)</td> <td>10.0%</td> <td>12.5%</td> <td>0402 0.068µF; 0603 0.68µF</td> </tr> <tr> <td>16V (C 1.0µF)</td> <td>12.5%</td> <td>---</td> <td>---</td> </tr> <tr> <td>10V</td> <td>15.0%</td> <td>---</td> <td>---</td> </tr> <tr> <td>6.3V</td> <td>30.0%</td> <td>---</td> <td>---</td> </tr> </tbody> </table> <ul style="list-style-type: none"> <li>* I.R.: 10V, 1G or 50 -F whichever is smaller. 6.3V, 10 -F</li> </ul>	Rated vol.	D.F.	Exception of D.F.		50V	3.0%	6.0%	0603 0.047µF; 0805 0.18µF, 1206 0.47µF	25V	5.0%	10.0%	0805 1µF, 1210 10µF	14.0%	0603 0.33µF	16V	5.0%	10.0%	0402 0.033µF; 0603 0.15µF; 0805 0.68µF; 1206 2.2µF	15.0%	0402 0.056µF; 0603 0.33µF; 0805 2.2µF; 1206 2.2µF TT series & Cap 1µF	6.3V	15.0%	30.0%	0805 10µF; 1210 100µF	Rated vol.	D.F.	Exception of D.F.		50V	7.5%	---	---	35V	10.0%	---	---	25V	7.5%	10.0%	0603 0.1µF; 0805 0.33µF; 1206 1µF; 1210 4.7µF	12.5%	0402 0.068µF	16V (C<1.0µF)	10.0%	12.5%	0402 0.068µF; 0603 0.68µF	16V (C 1.0µF)	12.5%	---	---	10V	15.0%	---	---	6.3V	30.0%	---	---
Rated vol.	D.F.	Exception of D.F.																																																											
50V	3.0%	6.0%	0603 0.047µF; 0805 0.18µF, 1206 0.47µF																																																										
25V	5.0%	10.0%	0805 1µF, 1210 10µF																																																										
		14.0%	0603 0.33µF																																																										
16V	5.0%	10.0%	0402 0.033µF; 0603 0.15µF; 0805 0.68µF; 1206 2.2µF																																																										
		15.0%	0402 0.056µF; 0603 0.33µF; 0805 2.2µF; 1206 2.2µF TT series & Cap 1µF																																																										
6.3V	15.0%	30.0%	0805 10µF; 1210 100µF																																																										
Rated vol.	D.F.	Exception of D.F.																																																											
50V	7.5%	---	---																																																										
35V	10.0%	---	---																																																										
25V	7.5%	10.0%	0603 0.1µF; 0805 0.33µF; 1206 1µF; 1210 4.7µF																																																										
		12.5%	0402 0.068µF																																																										
16V (C<1.0µF)	10.0%	12.5%	0402 0.068µF; 0603 0.68µF																																																										
16V (C 1.0µF)	12.5%	---	---																																																										
10V	15.0%	---	---																																																										
6.3V	30.0%	---	---																																																										

# Appendix II : General Information

## Construction

No.	Name	NP0/X7R	X7R/X5R/Y5V
①	Ceramic material	BaTiO <sub>3</sub> based	
②	Inner electrode	AgPd alloy	Ni
③	Termination	Inner layer	Ag
④		Middle layer	Ni
⑤		Outer layer	Sn (Matt)



## Storage and handling conditions

- (1) To store products at 5 to 40°C ambient temperature and 20 to 70% related humidity conditions.
- (2) The product is recommended to be used within one year after shipment. Check solderability in case of shelf life extension is needed.

### Cautions:

- Don't store products in a corrosive environment such as sulfide, chloride gas, or acid. It may cause oxidization of electrode, which easily be resulted in poor soldering.
- To store products on the shelf and avoid exposure to moisture.
- Don't expose products to excessive shock, vibration, direct sunlight and so on.

## Recommended soldering conditions

The lead-free termination MLCCs are not only to be used on SMT against lead-free solder paste, but also suitable against lead-containing solder paste. If the optimized solder joint is requested, increasing soldering time, temperature and concentration of N<sub>2</sub> within oven are recommended.




Fig. 2 IR reflow soldering profile for SMT process with SnAgCu series solder paste.




Fig. 3 IR reflow soldering profile for SMT process with eutectic SnPb solder paste.